MÖLLER-CHEMIE STEINPFLEGEMITTEL GmbH
ZIEGELTALSTRASSE 2
D-93346 IHRLERSTEIN
TELEFON 09441-176940
TELEFAX 09441-1769499
www.moellerstonecare.eu
info@moellerstonecare.eu



MOELLER STONE CARE

PORCELAIN TILES

TI-14.1

- cleaning and maintenance -

Care instruction tested

CONDITIONS

When treating a newly laid surface ensure sufficient drying time for the moisture to escape from the surface and substructure (maximum 2-4% residual moisture content).

Allow 2-3 weeks drying time for an adhesive bed and 4-6 weeks for mortar bed.

Drying times are indicative only and are subject to variation depending on the weather and the object and can be longer.

It's essential that any under-floor heating has been switched off and the surface is at a normal temperature, adequately cleaned, free of stains, dry and absorbent.

Always test in an inconspicuous place to determine suitability and coverage. Always read the labels carefully. Ensure the area around the surface to be treated is well ventilated.

CLEANING

 Construction dirt:
 R161
 Porcelain Tile Intensive Cleaner
 Coverage:
 approx.
 10-80 m²/litre

 Cement smears:
 R163
 Cement Film Remover
 Coverage:
 approx.
 5-50 m²/litre

Stains: Refer to Technical Information Sheet No. 1

After cleaning the surface must be allowed to dry for at least 1 to 2 days to a residual moisture content of 2-4% before any further treatment can take place.

PROTECTION - inside and outside

Basic protection: S243 Porcelain Tile Impregnator Coverage: approx. 15-30 m²/litre

Once dry the residual material is not harmful to health. Therefore impregnators can be used on kitchen tops.

MAINTENANCE - inside and outside

Regular maintenance: P315 Porcelain Tile Care Cleaner

add approx. 25 ml for every 10 liters of wash water

Periodical intensive cleaning: R157 Ceramic Tile Intensive Cleaner

periodical if necessary do a cleaning with soft brush

OLD SURFACES

Films of maintenance

products and dirt:

R157 Ceramic Tile Intensive Cleaner

Coverage: approx. 10-80 m²/litre

Layer of Waxes:

R154 Stripper - Stain Remover

Coverage: approx. 5-10 m²/litre

For optimum results and durability of further applications, older surfaces should be thoroughly cleaned. Repeat cleaning if necessary. After necessary drying time is allowed, proceed with products indicated under "PROTECTION". Always follow individual product directions.

ENVIRONMENT

All specialist products comply with the German Detergent Act and are registered with the Federal Environmental Offices in Berlin.

Our specialized products have been recommended for decades by leading porcelain tiles producers.

This technical instruction card is for advice only and is supplied without obligation. We require that the person making the application adapts all data concerning the application of the products to local conditions and the materials to be cleaned. We reserve the right to make changes to our products without warning as a result of technological advancement. The person conducting the application is responsible for any third person liabilities and ensuring compliance with any local laws or regu-

Your local dealer:

All products are available from many reputable natural stone and tile dealers.

© MOLLER STONE CARE GB-01.13