

MÖLLER-CHEMIE STEINPFLEGEMITTEL GmbH  
 ZIEGELTALSTRASSE 2  
 D-93346 IHRLEINSTEIN  
 TELEFON 09441-176940  
 TELEFAX 09441-1769499  
 www.moellerstonecare.eu  
 info@moellerstonecare.eu

# MOELLER STONE CARE



## PRODUCT SPECIFICATION

### HMK® S242 - COLOR ENHANCER

- **Protection and maintenance impregnator for all natural and artificial stone surfaces.**
  - **For polished, honed and textured finishes.**
  - **Reduces the penetration of water and dirt.**
- **The color and structure of the surface will be significantly enhanced.**
  - **For interior and exterior use.**

HMK® S242 is a ready to use special impregnator that reduces the penetration of water and dirt on all natural stone surfaces (soft and hard stones), agglomerates and terrazzo. For interior and exterior use. HMK® S242 can be used on polished, honed and textured surfaces. The color and structure of the surface will be significantly enhanced.

**Instructions:** If under floor heating exists, switch it off and allow the surface to cool. Clean stone surface thoroughly and let it dry (max residual moisture of 2-4%). Apply HMK® S242 generously and evenly with a soft paintbrush, roller with short fibres or HMK® Z950-Z951 Application Brushes. Repeat treatment for very absorbent surfaces after 24 hours. For less absorbent surfaces, remove excess with a paper towel before it dries. Smears left after the application process can be loosened and wiped off by using a soft clean cloth moistened with some more HMK® S242. Once dry the residual material is not harmful to health.

To clean surface thoroughly before treatment use HMK® R155 Intensive Cleaner - acid free.

For regular cleaning and continued protection use HMK® P324 Liquid Stone Soap, a no-rinse natural product.

**Drying time:** Dependent upon room temperature and ventilation, around 4 to 6 hours.

**Important:** Do not walk on the treated surface until treatment is complete. Protect surface from rain and humidity for 12 hours after treatment is completed. Do not apply to rubber, plastic, lacquered or varnished surfaces and solvent intolerant materials. Remove all foodstuffs from the area to be treated before work is commenced.

**Coverage:** About 5-20m<sup>2</sup>/litre depending on the nature of the surface.

**Warning:** Chemical product. Contains turpentine substitute. Flammable. Keep away from heat, sparks and flame. Harmful or fatal if swallowed or inhaled. Ensure the area to be treated is adequately ventilated. Avoid eye/skin contact. If exposed wash/flush with water and seek medical attention immediately. Remove all foodstuffs before beginning treatment. Once treatment is dry HMK® S242 is harmless to health. Keep out of the reach of children. See Material Safety Data Sheet for more detailed information.

**Packaging:** 12 x 1 litre bottles/box; 2 x 5 litre cans/box; 2 x 10 litre cans/box.

**Storage:** Store in a cool place and keep lid tightly closed.

**Testing:** Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12° and above 25°C.

**Limitation of liability:** The liability of HMK® Moeller Stone Care for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stone Care shall not be liable for any consequential damages. No other warranty or representation is made or implied.